



Amplify™/MC  
High Solids  
Floor Finish  
Powered by  
FrescoMax  
Technology

A high solids UHS floor finish for floors that demand excellent gloss and durability.

Features

- Applies easily and levels perfectly with no mop drag
- Great mark resistance and durability
- Solids Content 25%

Benefits

- Install up to five coats in one night
- Excellent reparability with spray buffing and burnishing
- Low odor finish is ideal for 24-hour facilities

Applications

- For use on resilient and most hard surface flooring. A sealer may be required for highly polished stone surfaces, glazed ceramic tile, luxury vinyl tile, and some rubber floors. Not intended for use on cork, wood, or bamboo flooring



# Amplify™/MC High Solids Floor Finish

Powered by FrescoMax Technology



## Use Directions

### Preparation

- Always barricade area to be finished.
- Before the first application of Amplify™/MC High Solids Floor Finish, remove all old finish with recommended Diversey stripper.

### Coating

- Apply 3 or more medium coats of Amplify™/MC High Solids Floor Finish with a clean finish mop. Let dry to the touch between coats (about 30 minutes).
- On porous or stone floors, seal first with 2 coats of recommended Diversey sealer.

### Maintenance

- Clean Daily: Dust mop. Then wet clean with recommended Diversey cleaner in an autoscrubber or with a damp mop.
- Spray buff as needed with recommended Diversey spray buff, a red or beige pad and a 175–1500 RPM machine. Or burnish with a UHS pad and a battery, cord electric or propane machine at 1500–2000+ RPM.
- Burnishing with Cleaner/Maintainer: Clean and restore gloss with recommended Diversey Cleaner/Maintainer using an autoscrubber or damp mop, let floor dry and then burnish.

### Recoating

- Clean thoroughly. Dust mop. Machine scrub with a floor machine or autoscrubber using a blue pad and the recommended Diversey cleaner at the recommended dilution. Rinse well and let dry.
- Apply 2 new coats of Amplify™/MC High Solids Floor Finish.

## Product Specifications

Description	
Certifications	None
Color/Form	Opaque White Liquid
pH	8.2
Scent	Product specific
Shelf Life	2 years

## Available Items

Product Code	Description/Package Size	Dilution
4972034	1 x 2.5 L / 2.64 Qt. ProSpeed™/MC BIB (Bag-in-Box)	Ready-to-Use
4385110	4 x 1 gallon / 3.78 L Containers	Ready-to-Use
5104714	1 x 5 gallon / 18.9 L Envirobox™/MC	Ready-to-Use

## Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at [www.sealedair.com](http://www.sealedair.com) or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.